




# GLOBAL SYN-TURF

GLOBAL SYN-TURF  
 2482 TECHNOLOGY DR  
 HAYWARD, CA 94545  
 TOLL FREE: 1-877-796-8873  
 FAX: (510) 732-6188  
 www.globalsynturf.com



SOD STAPLE 6" x 1" x 6"  
 DRAINAGE PASS THROUGH FOR WATER IN PUNCHED HOLES THROUGHOUT BACKING


SEAMING TAPE  
**SPECIFICATIONS**

YARN TYPE POLYETHYLENE C SHAPE BLADE  
 THATCH YARN TYPE POLYPROPYLENE CURLED AS THATCH  
 PILE HEIGHT 1 7/8"  
 TURF GAUGE 3/8"  
 FACE WEIGHT 60 OZ YD<sup>2</sup>  
 BACKING WEIGHT 24 OZ YD<sup>2</sup>  
 TOTAL WEIGHT 84 OZ YD<sup>2</sup>  
 STITCH RATE 6.9/10 CM  
 STITCHES/M<sup>2</sup> 7245

COLOR FIELD GREEN AND OLIVE GREEN AND GREEN WITH BROWN AND GREEN THATCHING

ROLL SIZE (FEET) 15' x 100'


MAXIMUM DRAIN RATE >30 INCHES PER HOUR



SECTION



**SEAMING**  
 SOD STAPLES ARE RECOMMENDED TO SEAM THE SEAMS




**SECURING TURF TO BASE**  
 BRIGHT COMMON 40D/60D NAILS OR GALVANIZED NAILS 6' APART ALONG PERIMETER SEAMS.



POWER BROOM AFTER INSTALLATION IS COMPLETE

**NOTES:**

1. THE GRASS MUST BE INSTALLED AND SEAMED WITH ADJACENT PIECES RUNNING IN THE SAME DIRECTION. SEAMS SHOULD BE GLUED WITH SUITABLE SEAMING GLUE AND SEAMING CLOTH, OR GST RECOMMENDED SEAMING TECHNIQUES.
2. COLOR: FIELD GREEN AND OLIVE GREEN AND GREEN WITH BROWN AND GREEN THATCHING.
3. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
4. DO NOT SCALE DRAWING.
5. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
6. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
7. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 5006-020.



## PERFORMANCE SERIES | ENGINEERED BLADES

PATRIOT CBLADE-84