




GLOBAL SYN-TURF


GLOBAL SYN-TURF
 5960 Inglewood Dr. #150
 Pleasanton, CA 94588
 TOLL FREE: 1-877-796-8873
 FAX: (510) 732-6188
 www.globalsynturf.com



SOD STAPLE 6" x 1" x 6"
 DRAINAGE PASS THROUGH FOR WATER IN PUNCHED HOLES THROUGHOUT BACKING

SEAMING TAPE
SPECIFICATIONS


YARN TYPE POLYETHYLENE S SHAPE BLADE
 THATCH YARN TYPE POLYPROPYLENE CURLED AS THATCH
 PILE HEIGHT 1 3/4"
 TURF GAUGE 5/8"
 FACE WEIGHT 66 OZ YD²
 BACKING WEIGHT 27 OZ YD²
 TOTAL WEIGHT 93 OZ YD²
 STITCH RATE 22/10 CM
 STITCHES/M² 13860
 COLOR EMERALD GREEN AND OLIVE GREEN WITH BROWN AND GREEN THATCHING
 ROLL SIZE (FEET) 15' x 100', 15' x 75'
 MAXIMUM DRAIN RATE >30 INCHES PER HOUR



SECTION



SEAMING
 SOD STAPLES ARE RECOMMENDED TO SEAM THE SEAMS




SECURING TURF TO BASE
 BRIGHT COMMON 40D/60D NAILS OR GALVANIZED NAILS 6' APART ALONG PERIMETER SEAMS.



POWER BROOM AFTER INSTALLATION IS COMPLETE

NOTES:

1. THE GRASS MUST BE INSTALLED AND SEAMED WITH ADJACENT PIECES RUNNING IN THE SAME DIRECTION. SEAMS SHOULD BE GLUED WITH SUITABLE SEAMING GLUE AND SEAMING CLOTH, OR GST RECOMMENDED SEAMING TECHNIQUES.
2. COLOR: EMERALD GREEN AND OLIVE GREEN WITH BROWN AND GREEN THATCHING.
3. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
4. DO NOT SCALE DRAWING.
5. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
6. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.



PERFORMANCE SERIES | ENGINEERED BLADES

S BLADE-66