

GLOBAL SYN-TURF

GREENING PLANET EARTH

Product Specification Sheet

Emerald-92 Stemgrass





BA USES


- Landscape
- Lawns
- Playgrounds
- Traffic Medians
- Pet Areas
- Commercial or Residential
- ► Light-Heavy Traffic



15 Year Manufacturer's Warranty8 Year Manufacturer's High Traffic Warranty



Flo-Rite Drainage Technology



STEMGRASS BLADE

SPECIFICATIONS

Pile Height: 1-7/8"

Turf Gauge: 3/8"

Face Weight: 92 oz./yd²

Backing Weight: 26 oz./yd²

Total Weight: 118 oz./yd²

Stitch Rate: 18.5/10cm

Stitches/M2: 19425

Material/Dtex: PE & PP16400

Color: Emerald Green with Brown and Green

Thatching

Type Of Fiber: **PE Monofilament and PP Curled**

As Thatch

Infill Amount: 1.0 lb./psf.

Primary Backing: Premium GST Backing

Tuft Bind: 10 lb/force (ASTM D1335)

Blade Type: Stemgrass Blade

Permeability: 162.3 inches/hr. (ASTM F1551)

Melting Point: 176 °F (ASTM D2859)

Grab Tear MD: >200 lb./force (ASTM D5034)

Grab Tear CMD: >200 lb./force (ASTM D5034)

Roll Width: 15 ft

Roll Length: **75 ft**

Sq. Ft. Per Roll: 1125

Total Roll Weight: 1214 lbs





