

GLOBAL SYN-T

Product Specification Sheet

Full Recycle-91





III USES


- Landscape
- Lawns
- **Playgrounds**
- **Traffic Medians**
- Pet Areas
- Commercial or Residential
- Light-Heavy Traffic



15 Year Manufacturer's Warranty 8 Year Manufacturer's High Traffic Warranty



Flo-Rite Drainage Technology



DOUBLE W BLADE

SPECIFICATIONS

Pile Height: 1.63"

Turf Gauge: 3/8"

Face Weight: 75 oz./yd²

Backing Weight: 16 oz./yd²

Total Weight: 91 oz./yd²

Stitch Rate: 17/10cm

Stitches/M2: 17850

Material/Dtex: PE10600 + PP4500

Color: Field Green & Olive Green with Brown

and Green Thatching

Type Of Fiber: PE monofilament and PP Curled

As Thatch

Infill Amount: 1.0 lb./psf.

Primary Backing: Premium GST Backing

Tuft Bind: 10+ lb/force (ASTM D1335)

Blade Type: Double W Blade

Permeability: 58.4 inches/hr. (ASTM F1551)

Melting Point: 176 °F (ASTM D2859)

Grab Tear MD: >200 lb./force (ASTM D5034)

Grab Tear CMD: >200 lb./force (ASTM D5034)

Roll Width: 15 ft

Roll Length: 100 ft

Sq. Ft. Per Roll: 1500

Total Roll Weight: 949 lbs





