




# GLOBAL SYN-TURF


GLOBAL SYN-TURF  
 5960 Inglewood Dr. #150  
 Pleasanton, CA 94588  
 TOLL FREE: 1-877-796-8873  
 FAX: (510) 732-6188  
 www.globalsynturf.com



SOD STAPLE 6" x 1" x 6"  
 DRAINAGE PASS THROUGH FOR WATER IN PUNCHED HOLES THROUGHOUT BACKING

SEAMING TAPE  
 SPECIFICATIONS


YARN TYPE POLYETHYLENE STEMGRASS BLADE  
 THATCH YARN TYPE POLYPROPYLENE CURLED AS THATCH  
 PILE HEIGHT 1 1/4"  
 TURF GAUGE 3/8"  
 FACE WEIGHT 63 OZ YD<sup>2</sup>  
 BACKING WEIGHT 29 OZ YD<sup>2</sup>  
 TOTAL WEIGHT 92 OZ YD<sup>2</sup>  
 STITCH RATE 16/10 CM  
 STITCHES/M<sup>2</sup> 16800  
 COLOR EMERALD GREEN AND OLIVE GREEN WITH GREEN THATCHING  
 ROLL SIZE (FEET) 15' X 100'  
 MAXIMUM DRAIN RATE >30 INCHES PER HOUR



SECTION



SEAMING  
 SOD STAPLES ARE RECOMMENDED TO SEAM THE SEAMS




SECURING TURF TO BASE  
 BRIGHT COMMON 40D/60D NAILS OR GALVANIZED NAILS 6' APART ALONG PERIMETER SEAMS.



POWER BROOM AFTER INSTALLATION IS COMPLETE

NOTES:

1. THE GRASS MUST BE INSTALLED AND SEAMED WITH ADJACENT PIECES RUNNING IN THE SAME DIRECTION. SEAMS SHOULD BE GLUED WITH SUITABLE SEAMING GLUE AND SEAMING CLOTH, OR GST RECOMMENDED SEAMING TECHNIQUES.
2. COLOR: EMERALD GREEN AND OLIVE GREEN WITH GREEN THATCHING.
3. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
4. DO NOT SCALE DRAWING.
5. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
6. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.



## OTHER TURF

TRAINERS TURF-63